



Product Fiche compliant to commission delegated regulation (EU) No 65/2014

Brand	SCHNEIDER
Model	SHIC 409 X
EEI [%] Energy Efficiency Index - Main cavity ¹⁾ EEI [%] Energy Efficiency Index - Main cavity 1)	100,36
EEI [%] Energy Efficiency Index - Secondary cavity ¹⁾ EEI [%] Energy Efficiency Index - Secondary cavity 1)	-
Energy Efficiency Class - Main cavity ²⁾ Energy Efficiency Class - Main cavity 2)	A
Energy Efficiency Class - Secondary cavity ²⁾ Energy Efficiency Class - Secondary cavity 2)	-
Energy consumption in conventional mode [kWh/cycle] - Main cavity ³⁾ Energy consumption in conventional mode [kWh/cycle] - Main cavity 3)	0,82
Energy consumption in conventional mode [kWh/cycle] - Secondary cavity ³⁾ Energy consumption in conventional mode [kWh/cycle] - Secondary cavity 3)	-
Energy consumption in fan-forced mode [kWh/cycle] - Main cavity ³⁾ Energy consumption in fan-forced mode [kWh/cycle] - Main cavity 3)	-
Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity ³⁾ Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity 3)	-
Energy consumption in conventional mode [MJ/cycle] - Main cavity ³⁾ Energy consumption in conventional mode [MJ/cycle] - Main cavity 3)	-
Energy consumption in conventional mode [MJ/cycle] - Secondary cavity ³⁾ Energy consumption in conventional mode [MJ/cycle] - Secondary cavity 3)	-
Energy consumption in fan-forced mode [MJ/cycle] - Main cavity ³⁾ Energy consumption in fan-forced mode [MJ/cycle] - Main cavity 3)	-
Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity ³⁾ Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity 3)	-
Number of cavities	1
Heat source - Main cavity	electricity
Heat Source - Secondary cavity	-
Usable volume [l] - Main cavity	65
Usable volume [l] - Secondary cavity	-
¹⁾ Energy Efficiency Index calculated according to the volume and energy consumption for each cavity. A+++ (low consumption) to D (high consumption). results of standards tests that simulate the thermal properties of food. The consumption will depend on how the appliance is used.	
²⁾ From ³⁾ Based on the	

Product Information compliant to commission regulation (EU) No 66/2014			
	Symbol	Value	Unit
Model identification		Built-in oven	
Type of oven		SHIC 409 B	
Mass of the appliance	M	38	kg
Number of cavities		1	
Heat source per cavity (electricity or gas)		electricity	
Volume per cavity - Main cavity	V	65	lt
Volume per cavity - Secondary cavity	-	-	-
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Main cavity	EC _{electric cavity} EC _{electric cavity}	0,82	kWh/cycle
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity} EC _{electric cavity}	-	-
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Main cavity	EC _{electric cavity} EC _{electric cavity}	-	-
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity} EC _{electric cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity ¹⁾ Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity 1)	EC _{gas cavity} EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity	EC _{gas cavity} EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity ¹⁾ Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity 1)	EC _{gas cavity} EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity ¹⁾	EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity	EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity ¹⁾	EC _{gas cavity}	-	-
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}	-	-
Energy Efficiency Index per cavity - Main cavity	EEI _{cavity}	100,36	MJ/cycle kWh/cycle (1)
Energy Efficiency Index per cavity - Secondary cavity	EEI _{cavity}	-	-

¹⁾ 1kWh/cycle = 3,6 MJ/cycle